



COMMERCIAL - TECHNICAL DATA / Tecnologia

FABRIC NAME

DENVER

YARN/CONSTRUCTION:	21/2S(POLY SPUN)*21/2S(POLY SPUN)	COMP:	100%POLY SPUN
		H.S CODE	55121900
Test Method for Woven Fabrics			STANDARD (WHITE 00)
Width / Ancho NTC 228-2011	Phisic / Fisico	In 61	Cms 155
	Useful / Util	59	150
Weight /Peso ASTM D 3776-2009		Oz/syd 7.8	Gsm 266
	Shrinkage / Cambio dimensional (%) AATCC 135-2004 / IN504-15	Lenght / Longitud Trans / Transversal	5% 5%
Spirality after laundry / Viraje despues del lavado (%) ISO16322-2-2005	Lenght / Longitud	2%	
	Trans / Transversal		
Color fastness to wash / Solidez al lavado (gray scale) AATCC 61-2007	Change / Cambio	4	
	Stain / Transf	4	
Dye transfer to storage. Option II (gray scale) / Transferencia del color por almacenamiento. Opcion II AATCC 163-2007	Stain / Transf	4	
Color fastness to light (gray scale) / Solidez a la luz BS 1006-1990	Change / Cambio	3	
Color fastness to crocking (gray scale) / Solidez al frote AATCC 8-2007	Dry / Seco	4	
	Wet / Húmedo	3	
Color Fastness to perspiration (gray scale) / Solidez a la transpiración AATCC 15-2007	Change / Cambio	4	
	Stain / Transf	4	
Pilling / Pilling (Photographic) NTC 2051-2 / 2003	3		
Type of fabric / Tipo de tejido	Woven		

Recommendations:

