



COMMERCIAL - TECHNICAL DATA / Tecnologia

FABRIC NAME

SOFT SHELL SPANDEX

YARN/CONSTRUCTION:	Face:100D+40d*100D+40d/127 *83 Back:150D(DTY)144F	COMP:	Face:90%Poly/10%Span. Back:100%Poly
		H.S CODE	54077100
Test Method for Knit Fabrics			STANDARD (WHITE 00)
Width / Ancho NTC 228-2011	Phisic / Fisico	In 57	Cms 145
	Useful / Util	57	145
Weight /Peso ASTM D 3776-2009		Oz/syd 9.7	Gsm 330
	Shrinkage / Cambio dimensional (%) AATCC 135-2004 / IN504-15	Lenght / Longitud Trans / Transversal	4% 4%
Spirality after laundry / Viraje despues del lavado (%) ISO16322-2-2005	Lenght / Longitud		2%
	Trans / Transversal		
Color fastness to wash / Solidez al lavado (gray scale) AATCC 61-2007	Change / Cambio		4
	Stain / Transf		4
Dye transfer to storage. Option II (gray scale) / Transferencia del color por almacenamiento. Opcion II AATCC 163-2007	Stain / Transf		4
Color fastness to light (gray scale) / Solidez a la luz BS 1006-1990	Change / Cambio		3
Color fastness to crocking (gray scale) / Solidez al frote AATCC 8-2007	Dry / Seco		4
	Wet / Húmedo		3
Color Fastness to perspiration (gray scale) / Solidez a la transpiración AATCC 15-2007	Change / Cambio		4
	Stain / Transf		4
Pilling / Pilling (Photographic) NTC 2051-2 / 2003			3
Type of fabric / Tipo de tejido			Knit

Recommendations:

