



**COMMERCIAL - TECHNICAL DATA / Tecnologia**

**FABRIC NAME**

**SPUN POLYESTER**

<b>YARN/CONSTRUCTION:</b>	<b>16S(VOTEX)*8S(VOTEX)</b>	<b>COMP:</b>	<b>100% POLY SPUN</b>
		<b>H.S CODE</b>	<b>55121900</b>
<b>Test Method for Woven Fabrics</b>			<b>STANDARD ( WHITE 00)</b>
Width / Ancho NTC 228-2011	Phisic / Fisico	<b>In</b> 64	<b>Cms</b> 162
	Useful / Util	61	155
Weight /Peso ASTM D 3776-2009		<b>Oz/syd</b> 6.5	<b>Gsm</b> 220
	Shrinkage / Cambio dimensional (%) AATCC 135-2004 / IN504-15	Lenght / Longitud Trans / Transversal	4% 4%
Spirality after laundry / Viraje despues del lavado (%) ISO16322-2-2005	Lenght / Longitud		2%
	Trans / Transversal		
Color fastness to wash / Solidez al lavado (gray scale) AATCC 61-2007	Change / Cambio		4
	Stain / Transf		4
Dye transfer to storage. Option II (gray scale) / Transferencia del color por almacenamiento. Opcion II AATCC 163-2007	Stain / Transf		4
Color fastness to light (gray scale) / Solidez a la luz BS 1006-1990	Change / Cambio		3
Color fastness to crocking (gray scale) / Solidez al frote AATCC 8-2007	Dry / Seco		4
	Wet / Húmedo		3
Color Fastness to perspiration (gray scale) / Solidez a la transpiración AATCC 15-2007	Change / Cambio		4
	Stain / Transf		4
Pilling / Pilling (Photographic) NTC 2051-2 / 2003			3
Type of fabric / Tipo de tejido			Woven

**Recommendations:**

