



COMMERCIAL - TECHNICAL DATA / Tecnologia

FABRIC NAME

VISCOSITY

YARN/CONSTRUCTION:	300d*2 (DTY)+21/2(Poly Spun) * 300d*2(DTY)+21/2(Poly Spun)	COMP:	100% POLY SPUN	
		H.S CODE	55121900	
Test Method for Woven Fabrics			STANDARD (WHITE 00)	
Width / Ancho NTC 228-2011			In	Cms
		Phisic / Fisico	61	155
		Useful / Util	59	150
Weight /Peso ASTM D 3776-2009			Oz/syd	Gsm
			8.7	295
Shrinkage / Cambio dimensional (%) AATCC 135-2004 / IN504-15		Lenght / Longitud	5%	
		Trans / Transversal	5%	
Spirality after laundry / Viraje despues del lavado (%) ISO16322-2-2005		Lenght / Longitud	2%	
		Trans / Transversal		
Color fastness to wash / Solidez al lavado (gray scale) AATCC 61-2007		Change / Cambio	4	
		Stain / Transf	4	
Dye transfer to storage. Option II (gray scale) / Transferencia del color por almacenamiento. Opcion II AATCC 163-2007		Stain / Transf	4	
Color fastness to light (gray scale) / Solidez a la luz BS 1006-1990		Change / Cambio	3	
Color fastness to crocking (gray scale) / Solidez al frote AATCC 8-2007		Dry / Seco	4	
		Wet / Húmedo	3	
Color Fastness to perspiration (gray scale) / Solidez a la transpiración AATCC 15-2007		Change / Cambio	4	
		Stain / Transf	4	
Pilling / Pilling (Photographic) NTC 2051-2 / 2003			3	
Type of fabric / Tipo de tejido			Woven	

Recommendations:

